

BACE Vertical Baler V63-865

This non-ferrous scrap baler produces more than 150,000 lbs. of compact force at more than 80 PSI of platent pressure. The 65" stroke cylinder provides maximum compaction, extending to within a few inches of the floor. Manufactured for tin, aluminum, brass, bronze, and other non-ferrous metals, it also bales paper, paper cores, plastics, and other recyclables.

Ideal for

- Grocery Stores
- Home Retailers
- Big Box Retailers
- National Accounts
- Commissaries
- Warehouses

- Distribution Centers
- Hospitals, Schools & Universities



Order Today: (877) 506-BACE or visit us online at www.bacecorp.com

200 Ratchford Rd. York, SC 29745

BACE Balers meet existing ANSI Standards and are ETL & CETL Approved.














BACE Vertical Baler V63-865

DIM. (in./mm)

- **A.** 53.5/1359
- **B.** 94/2388
- **C.** 47/1194
- **D.** 169.5/4305
- E. 96/2438







| SPECIFICATIONS | |
|------------------------|--------------------|
| | |
| PERFORMANCE | |
| Nominal Bale Size | 60" x 30" x 48" |
| Bale Weight | Up to 2000 lbs OCC |
| Bale Volume | 50 cu. ft. |
| No. of Bale Tie Slots | 5 |
| Compact Force lbs | 150,798 |
| Platen Pressure | 84 PSI |
| Average Cycle Time | 53 Seconds |
| Loading Height | 53.50" |
| Ejector System | Semi-Automatic |
| | |
| HYDRAULIC / ELECTRICAL | |

Available Options

- Slotted Front Door
- Wire Guides (allows for front bale tie-off)
- Feed Chute
- Counter WeightedFloppy Retainer Dogs
- Oil Heater
- Weather Proof Package

| Power Unit (side mount is standard) | 10 HP Submersible - Dual Pump with Regen |
|-------------------------------------|--|
| Voltage 3 Phase | 208V, 230V, 480V |
| Full Load Amps (A = Amps) | 32A, 28A, 14A |
| Pump GPM | 14/4 Dual Pump with Regen |
| Factory Set System Pressure PSI | 3000 |
| Cylinder Bore x Stroke | 8" x 65" |
| Hydraulic Tank Capacity Gallons | 60 |
| ADDITIONAL HYDRAULIC/ELECTF | RICAL CONFIGURATIONS ARE AVAILABLE. PLEASE CALL BACE FOR MORE INFORMATION. |